



**LX 320M**



**LX 120A  
LX 220A  
LX 320A**



**LX 4200C  
LX 3200D**

## General

The LX Range offers exceptional functionality, ergonomics and elegance, is easy to use and has excellent display readability. The scales are also very easy to clean.

The LX scales are also available with built-in functions such as auto calibration and adjustment.

## European conformity

- Directive 2004/108/CE for *Electromagnetic Compatibility*.
- Directive 2006/95/CE for *Low Voltage* equipments.

## Functions

- ▼ Parts counting
- ▼ Percentage
- ▼ Animal weighing
- ▼ Tolerance check +/-
- ▼ Unit conversion
- ▼ Statistics
- ▼ Totalising
- ▼ Density

## Main features

- ▼ Range
  - From 120 g to 4200 g depending on the model.
- ▼ Accuracy
  - From 0.0001 g to 1 g depending on the model.
- ▼ Keyboard
  - Illuminated touch-sensitive keys when function is active.
- ▼ Display unit
  - High-brightness blue LEDs
- ▼ Platform
  - Nickel-chrome steel.
- ▼ Power supply
  - 230 V AC.
  - Accumulator (optional).
- ▼ Protection
  - IP 54.

## Other equipment

Standard:

- Date/time.
- RS 232 and USB links

Optional:

- Built-in auto calibration system.

## Technical data

### ▼ Dimensions and weight

Models			Width (mm)	Depth (mm)	Height (mm)	Weight (kg)
LX 120A	LX 220A	LX 320A	228	381	342	6.6
LX 320M			228	381	124	5.5
LX 4200C	LX 3200D		228	381	90	5.6

### ▼ Power supply

- Voltage ..... 90 - 264 V
- Frequency ..... 47 - 63 Hz
- Power consumption ..... 18 VA

### ▼ Operation

- Temperature range ..... +5 / + 40°C

## Available models

Models	Capacity (g)	Accuracy (g)	Division (g)	Platform dimensions (mm)
LX 120A	120	0.0001	0.001	Ø 90
LX 220A	220	0.0001	0.001	Ø 90
LX 320A	320	0.0001	0.001	Ø 90
LX 320M	320	0.001	0.01	135 x 135
LX 4200C	4200	0.01	0.1	200 x 200
LX 3200D	3200	0.1	0.1	200 x 200